

General Warnings

- Loading ramps are intended solely for transporting a vehicle onto/off a transport vehicle.
- The ramps are designed to be used at low and smooth speeds, up to a maximum of 3 km/h.
- The weight of the transported vehicle must not exceed the maximum load capacity specified in the product description.
- The loading platform must not be higher than 80 cm.
- Do not handle the ramp or the transported vehicle under the influence of alcohol or other intoxicating substances.
- Failure to follow these instructions may result in property damage (to the transported vehicle, the ramp, or the transport vehicle) and personal injury.

Instructions for Use in the Unfolded State

- If the ramp is foldable, visually inspect the hinge mechanism pin before use. The pin must be tightened and secure.
- Place the braked vehicle with the loading platform on a flat and stable surface.
- Position the ramps so that their ends are in full contact with the loading platform.
- Do not use the ramps for loading onto a surface higher than the specified maximum height of 80 cm.
- If using multiple ramps, place them side by side on the loading platform, spaced according to the wheel track of the two-track vehicle.
- Ensure that the contact parts of the ramps are securely supported by the edge of the loading platform.
- Drive the transported vehicle onto the ramp at a low (max. 3 km/h) and constant speed, centered along the ramp's width, throughout the entire loading or unloading process.
- Actively monitor the entire vehicle loading process.
- Use the brakes of the transported vehicle when necessary to ensure completely smooth movement along the ramp(s).
- When loading a motorcycle, guide it manually — do not sit on it.
- Avoid any jerky or uneven movements on the ramp(s).
- Avoid turning the vehicle on the ramp(s).
- Avoid excessive acceleration or deceleration of the transported vehicle on the ramps.
- When loading/unloading the vehicle, avoid excessive tilting from its vertical axis, as this may result in loss of control.
- The ramp(s) are suitable for loading motorcycles, ATVs, UTVs, SBS, and wheeled garden equipment.
- The ramp(s) are not suitable for loading skid-steered or tracked vehicles, where smooth movement cannot be ensured.